

# PRODUCT INFORMATION SUMMARY

## K070 : D-SOLVE

heavy duty graffiti remover

### Description of product

Powerful fast acting formula. Gel form helps prevent run-off from vertical surfaces. Water soluble - simply wash off with water. Ozone friendly. Does not contain chlorofluorocarbons. Low odour, no choking fumes.

### Product Uses

Rapidly dissolves or breaks up all forms of graffiti. The strong solvent action works on felt tip, ball point, crayon, spray paint (cellulose, acrylic or polyurethane). Floor paints and varnishes are also dissolved by the powerful action of D-Solve.

### Directions

Spray D-Solve onto the surface affected. Leave for between 30 seconds and 10 minutes then wipe off, wash off or scrape off depending on which is more appropriate. Solvent sensitive surfaces will be softened or dissolved by this product i.e. paints, some plastics, some fabrics. Always test a small inconspicuous area for resistance to this product before commencing work. Typical contact times: Ball Point 30-60 seconds Felt tip pens 30-60 seconds Crayon 1-3 minutes Aerosol paint 1-5 minutes Varnish 10-20 minutes

### iN Insight Supported

iN Insight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



typical dilution

### iN Insight recommended product uses

Special - graffiti removal from porous surfaces (eg. brickwork)

n/a

### Product Hazards and PPE Requirements

Danger



Contains : D-limonene

### Risk Phrases

Extremely flammable aerosol. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects. Pressurised container: May burst if heated.

### Safety Phrases

Keep out of reach of children. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

### Technical Data

Composition	Water dispersable organic solvents, natural citrus oils, thickeners and stabilisers.
Appearance	Turbid liquid
Colour	straw coloured
Density	0.87
Fragrance	Citrus
Stability	Two years minimum
Storage	Pressurised container. Store out of direct sunlight. Temperature must not exceed 50oC

### Aerosol Information

Propellant	Hydrocarbon
Pressure	49 psi
Spray Rate	3.2

### Environmental Profile

#### Biodegradability

#### Selden Environmental Charter

- We set ourselves industry leading standards.
  - Selden minimises wastage, packaging and transportation.
  - If it can be recycled, it will be recycled.
  - Our chemicals policy exceeds regulatory requirements.
  - We don't expect other people to clean up after us.
  - Conserving energy, preserving resources.
  - By being innovative, we strive to do better.
  - We like to work in partnership with our clients.
- Visit our website for more information.

#### External Accreditations

9001 - Quality System  
14001 - Environmental System  
18001 - Health & Safety System  
IPPC Certified Manufacturer

#### Sustainability

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



### COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



### www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



UKAS  
accredited testing  
laboratory No. 4204



**SELDEN**  
formulating  
testing  
manufacturing  
to  
the highest  
standards

### Selden Research Limited

Staden Business Park, Staden Lane, Buxton  
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : [info@selden.co.uk](mailto:info@selden.co.uk) | web : [www.selden.co.uk](http://www.selden.co.uk)

